

| Name | Description | Your Servers | | |
|------------------------|--|--------------|----------|----------|
| | | Server 1 | Server 2 | Server 3 |
| INFORMIXSERVER | The name of an Informix database server on the network | | | |
| NETTYPE Protocol | Nettype is an 8-character string specifying the protocol in this format: ddiiiPPP dd = Database product [ol on dr] iii = Interface type [ipc soc tli sql] PPP = Protocol [imc nmp shm spx str tcp ssl mux] | | | |
| Hostname or IP Address | Hostname is the name of the computer where the database server resides as listed in /etc/hosts or the IP address | | | |
| Service or Port Number | Service name is a service name entry from the services file /etc/services or the port number the database is listening for connection on IANA (www.iana.org) assigned port number/service names for Informix: sqlexec 9088/tcp sqlexec-ssl 9089/tcp | | | |
| Options | Optional Values examples: b=<connection buffer size> c=<connection redirection> g=<group name> i=<group identifier> e=<end of group> m=<multiplexed connection> k=<keep alive setting> r=<client security setting> s=<server security setting> csm=<communication support module> cfd=<communication files directory> | | | |
| Database | The Database Name to connect to on an Informix Server | | | |
| Username | User Login Name | | | |
| Password | User Login Password | | | |
| Data Source Name | ODBC Name for the Connection, may be User DSN or System DSN | | | |